



THE HF DRIVER



www.ztzspeaker.com

OUR GUIDE TO  
LOUDSPEAKER SPECIFICATIONS

Make It Louder



www.ztzspeaker.com

Email: ztzspeaker@gmail.com

Web : www.ztzspeaker.com

ZTZ SPEAKER

### DH350/DH450

| HF DRIVER           | 1 INCH      | 1 INCH      |
|---------------------|-------------|-------------|
| RMS Capacity        | 40 W        | 60 W        |
| Voice Coil Diameter | 1.35"/34 MM | 1.75"/44 MM |
| Frequency Response  | 1K-20K Hz   | 1K-20K Hz   |
| Sensitivity         | 106 dB      | 108 dB      |
| Impedance           | 8 Ohm       | 8 Ohm       |
| Magnet              | 13 Oz       | 33 Oz       |



### DH510/DH750

| HF DRIVER           | 2 INCH    | 2 INCH     |
|---------------------|-----------|------------|
| RMS Capacity        | 80 W      | 100 W      |
| Voice Coil Diameter | 2"/51 MM  | 3"/74 MM   |
| Frequency Response  | 1K-20K Hz | 800-18K Hz |
| Sensitivity         | 108 dB    | 108 dB     |
| Impedance           | 8 Ohm     | 8 Ohm      |
| Magnet              | 34 Oz     | 60 Oz      |

### NH350/NH450

| HF DRIVER           | 1 INCH      | 1 INCH      |
|---------------------|-------------|-------------|
| RMS Capacity        | 40 W        | 60 W        |
| Voice Coil Diameter | 1.35"/34 MM | 1.75"/44 MM |
| Frequency Response  | 1K-20K Hz   | 1K-20K Hz   |
| Sensitivity         | 106 dB      | 107 dB      |
| Impedance           | 8 Ohm       | 8 Ohm       |
| Magnet              | Neodymium   | Neodymium   |



### NH510/NH750

| HF DRIVER           | 1 INCH    | 1.5 INCH   |
|---------------------|-----------|------------|
| RMS Capacity        | 80 W      | 100 W      |
| Voice Coil Diameter | 2"/51 MM  | 3"/74 MM   |
| Frequency Response  | 1K-20K Hz | 800-18K Hz |
| Sensitivity         | 106 dB    | 106 dB     |
| Impedance           | 8 Ohm     | 8 Ohm      |
| Magnet              | Neodymium | Neodymium  |



### 10LW350/12LW350/15LW350

| PROFESSIONAL SPEAKER | 10 INCH    | 12 INCH    | 15 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 600 W      | 800 W      | 800 W      |
| Voice Coil Diameter  | 3.5"/89 MM | 3.5"/89 MM | 3.5"/89 MM |
| Frequency Response   | 63-4000 Hz | 50-4000 Hz | 48-4000 Hz |
| Sensitivity          | 97 dB      | 97 dB      | 98 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | 136 Oz     | 136 Oz     | 136 Oz     |



### 10FW350/12FW350/15FW350

| PROFESSIONAL SPEAKER | 10 INCH    | 12 INCH    | 15 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 600 W      | 600 W      | 700 W      |
| Voice Coil Diameter  | 3.5"/89 MM | 3.5"/89 MM | 3.5"/89 MM |
| Frequency Response   | 60-3200 Hz | 60-3000 Hz | 40-3000 Hz |
| Sensitivity          | 97 dB      | 97 dB      | 97 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | 107 Oz     | 107 Oz     | 107 Oz     |



### 8MD300/10MD300/12MD300

| PROFESSIONAL SPEAKER | 8 INCH     | 10 INCH    | 12 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 300 W      | 400 W      | 400 W      |
| Voice Coil Diameter  | 3"/75 MM   | 3"/75 MM   | 3"/75 MM   |
| Frequency Response   | 85-4200 Hz | 72-3500 Hz | 58-4000 Hz |
| Sensitivity          | 96 dB      | 97 dB      | 98 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | 75 Oz      | 97 Oz      | 97 Oz      |



### 10LW350N/12LW350N/15LW350N

| PROFESSIONAL SPEAKER | 10 INCH    | 12 INCH    | 15 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 600 W      | 800 W      | 800 W      |
| Voice Coil Diameter  | 3.5"/89 MM | 3.5"/89 MM | 3.5"/89 MM |
| Frequency Response   | 69-4000 Hz | 83-3500 Hz | 51-3500 Hz |
| Sensitivity          | 97 dB      | 97 dB      | 98 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | Neodymium  | Neodymium  | Neodymium  |



### 10FW350N/12FW350N/15FW350N

| PROFESSIONAL SPEAKER | 10 INCH    | 12 INCH    | 15 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 500 W      | 600 W      | 700 W      |
| Voice Coil Diameter  | 3.5"/89 MM | 3.5"/89 MM | 3.5"/89 MM |
| Frequency Response   | 64-4000 Hz | 61-3500 Hz | 56-3500 Hz |
| Sensitivity          | 97 dB      | 97 dB      | 98 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | Neodymium  | Neodymium  | Neodymium  |



### 8MD300N/10MD300N/12MD300N

| PROFESSIONAL SPEAKER | 8 INCH     | 10 INCH    | 12 INCH    |
|----------------------|------------|------------|------------|
| RMS Capacity         | 300 W      | 400 W      | 400 W      |
| Voice Coil Diameter  | 3"/75 MM   | 3"/75 MM   | 3"/75 MM   |
| Frequency Response   | 85-4500 Hz | 74-4000 Hz | 63-4000 Hz |
| Sensitivity          | 97 dB      | 98 dB      | 99 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | Neodymium  | Neodymium  | Neodymium  |



### 8MH200/10MH300/12MH300/15MH300

| PROFESSIONAL SPEAKER | 8 INCH     | 10 INCH    | 12 INCH    | 15 INCH    |
|----------------------|------------|------------|------------|------------|
| RMS Capacity         | 200 W      | 300 W      | 400W       | 500 W      |
| Voice Coil Diameter  | 2"/50 MM   | 3"/75 MM   | 3"/75 MM   | 3"/75 MM   |
| Frequency Response   | 85-5000 Hz | 65-6000 Hz | 54-4800 Hz | 56-4500 Hz |
| Sensitivity          | 96 dB      | 97 dB      | 98 dB      | 99 dB      |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm      | 8 Ohm      |
| Magnet               | 57 Oz      | 90 Oz      | 90 Oz      | 90 Oz      |



### 15LW400/18LW400/15LW451/18LW451

| PROFESSIONAL SPEAKER | 15 INCH    | 18 INCH    | 15 INCH     | 18 INCH     |
|----------------------|------------|------------|-------------|-------------|
| RMS Capacity         | 1000 W     | 1200 W     | 1200 W      | 1500 W      |
| Voice Coil Diameter  | 4"/100 MM  | 4"/100 MM  | 4.5"/114 MM | 4.5"/114 MM |
| Frequency Response   | 45-1500 Hz | 39-1500 Hz | 45-1200 Hz  | 35-1000 Hz  |
| Sensitivity          | 97 dB      | 97 dB      | 97 dB       | 97 dB       |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm       | 8 Ohm       |
| Magnet               | 150 Oz     | 150 Oz     | 200 Oz      | 200 Oz      |



### 15FW400/18FW400/15FW451/18FW451

| PROFESSIONAL SPEAKER | 15 INCH    | 18 INCH    | 15 INCH     | 18 INCH     |
|----------------------|------------|------------|-------------|-------------|
| RMS Capacity         | 1000 W     | 1000 W     | 1500 W      | 1800 W      |
| Voice Coil Diameter  | 4"/100 MM  | 4"/100 MM  | 4.5"/114 MM | 4.5"/114 MM |
| Frequency Response   | 41-2000 Hz | 33-1200 Hz | 38-1200 Hz  | 35-1000 Hz  |
| Sensitivity          | 97 dB      | 97 dB      | 97 dB       | 97 dB       |
| Impedance            | 8 Ohm      | 8 Ohm      | 8 Ohm       | 8 Ohm       |
| Magnet               | 125 Oz     | 125 Oz     | 200 Oz      | 200 Oz      |